




IKUSI


NEW RANGE

Indoor CATV taps and splitter 5-1000 MHz

- Zamak chassis with high-quality shielding
- Wall fixing holes
- Grounding facilities




DFC-410



DFC-415



DFC-420



DFC-425



DIFC-201

Taps 4 outputs

MODEL	DFC-410	DFC-415	DFC-420	DFC-425	
REF.	2086	2087	2088	2089	
Outputs	4				
Frequency range	5-1000 MHz				
Tap loss (± 1.5 dB)	dB				
	10	16	20	24	
Through loss	5-30 MHz	≤ 3.5	≤ 1.8	≤ 1.0	≤ 1.0
	30-470 MHz	≤ 3.6	≤ 1.8	≤ 1.1	≤ 0.8
	470-1000 MHz	≤ 4.5	≤ 2.5	≤ 1.5	≤ 1.2
Directional isolation	5-30 MHz	≥ 28	≥ 30	≥ 30	≥ 30
	30-470 MHz	≥ 27	≥ 28	≥ 28	≥ 28
	470-1000 MHz	≥ 25	≥ 25	≥ 25	≥ 25
Isolation between outputs	5-30 MHz	≥ 30	≥ 36	≥ 40	≥ 45
	30-470 MHz	≥ 28	≥ 32	≥ 33	≥ 33
	470-1000 MHz	≥ 25	≥ 27	≥ 27	≥ 30
Return loss	5-30 MHz	≥ 21	≥ 22	≥ 22	≥ 22
	30-470 MHz	≥ 20	≥ 20	≥ 20	≥ 20
	470-1000 MHz	≥ 17	≥ 17	≥ 17	≥ 17

Splitter 2 outputs

MODEL	DIFC-201	
REF.	2081	
Outputs	2	
Frequency range	5-1000 MHz	
Insertion loss	5-30 MHz	≤ 3.5
	30-470 MHz	≤ 3.6
	470-1000 MHz	≤ 4
Output isolation	5-30 MHz	≥ 30
	30-470 MHz	≥ 30
	470-1000 MHz	≥ 28
Return loss	5-30 MHz	≥ 21
	30-470 MHz	≥ 21
	470-1000 MHz	≥ 20