

Standalone Multiswitches (v.10)

MS0504

REF. 1023

MS0508

REF. 1024

MS0512

REF. 1025

MS0516

REF. 1026



Data Sheet



www.ikusi.com

- Star distribution of 4 SAT-IF polarizations plus terrestrial to 4, 8, 12 or 16 users.
- Active and passive mode of terrestrial band can be selected by the switches or potentiometer. The return path is available in the passive mode.
- Mains powered. F type connection.
- Indoor mounting. Wall fixing.

		MS-0504	MS-0508	MS-0512	MS-0516
Number of SAT inputs				4	
Number of outputs (users)		4	8	12	16
SAT frequency band	MHz			950 – 2300	
TERR frequency band active/passive	MHz			40-862 / 5-862	
TERR loss active/passive	dB	2/19	3/20	7/21	6/22
Max output level TERR active/passive	dBμV	91/81	90/80	92/79	91/78
Variable attenuator at SAT inputs	dB			0 – 15	
SAT output level (-35dB IMD3, EN 50083-3)	dBμV	97	96	90	90
Control by 10-14.5/15.5-20 V +0/22 kHz; + ToneBurst				Yes	
DISEqC 2.0 support				–	
Mains voltage (50 Hz)	VAC	230 ±10%		110 – 250	
Max consumption	VA		22		
Max LNBS current	mA		600		
Dimensions	mm	235 x 150 x 80		315 x 150 x 80	

