



User terminal box with 2 ports+pigtail connectorized at both ends



PAUF 2xxD



CFA-002D (8039)
Cable 2 tightened optical fibers
G657A2-LSZH



- Protected connectors for ducting with 20 mm diameter tube, with bending radius of 7 cm.
- Pre-connectorized pigtails at both ends for FTTH infrastructures.
- Includes a terminal box user with SC/SC APC connectors and adapters.
- Used cable is CFA-002D type with two adjusted fibers and tensile strength >450 N.
- Available in different lengths: 10, 15, 20, 25, 30, 40, 55 and 70 m of cable outside.
- Pull-box packaging

PAUF-200D Series								
MODEL	PAUF-210D	PAUF-215D	PAUF-220D	PAUF-225D	PAUF-230D	PAUF-240D	PAUF-255D	PAUF-270D
REF.	8011	8012	8013	8014	8015	8016	8017	8018
Cable length	10 meters	15 meters	20 meters	25 meters	30 meters	40 meters	55 meters	70 meters
Manufacturing material	ABS							
Degree of protection	IP44							
Dimensions	115 x 80 x 21 mm							
Plastic material	UL 94 V-0 (Flammability safety standard)							
Colour	White (RAL9003)							
Adapters	2 x SC/APC							
Accessories	2x M3 screw and plug + 2x Fusion protectors							
SC/SC Adapters								
Fiber type	SM							
Polished	APC							
Dust protection	Hinged lid with spring							
2-Fiber tight cable G657A2-LSZH CFA-002D								
Number of Fibers	2							
Core diameter and cladding	9 / 125 µm (124,8 ±0,7)							
Tight-fitting Fiber cover								
Diameter	850 µm ±50 µm							
Material	LSZH							
Colour	Green, red							
Outer cover								
Outer diameter	4 ±0.2 mm							
Thickness	0.8 mm ±0.05 mm							
Material	LSZH -FR							
CPR	Dca-s2, d2, a2							
Colour	Ivory RAL 1015							
Interior protection	Aramids							
SC Connectors								
Connector type	SC							
Polished	APC							
Connection type	Polished							
IL insertion loss	0.2 dB							