


User terminal box with 2 ports+pigtail connectorized at one end


CPR
Dca



PAUF 1xD



CFA-002D (8039)
Cable 2 tightened optical fibers
G657A2-LSZH



- Pigtail specially designed for FTTH infrastructures.
- Includes a user terminal box with SC/SC APC connectors and adapters.
- The cable used is of the type CFA-002D with two adjusted fibres and tensile strength >450 N.
- Available in different lengths: 10, 15, 20, 25, 30, 40, 55 and 70 m of cable outside.
- Pull-box packaging



PAUF-100D Series								
MODEL	PAUF-110D	PAUF-115D	PAUF-120D	PAUF-125D	PAUF-130D	PAUF-140D	PAUF-155D	PAUF-170D
REF.	8002	8003	8004	8005	8006	8007	8008	8009
Cable length	10 meters	15 meters	20 meters	25 meters	30 meters	40 meters	55 meters	70 meters
Manufacturing material	ABS							
Degree of protection	IP44							
Dimensions	115 x 80 x 21 mm							
Plastic material	UL 94 V-0 (Flammability safety standard)							
Colour	White (RAL9003)							
Adapters	2 x SC/APC							
Accessories	2x M3 screw and plug + 2x Fusion protectors							
SC/SC Adapters								
Fibre type	SM							
Polished	APC							
Dust protection	Hinged lid with spring							
2-fiber tight cable G657A2-LSZH CFA-002D								
Number of fibers	2							
Core diameter and cladding	9 / 125 µm (124.8 ±0,7)							
Tight-fitting fiber cover								
Diameter	850 µm ±50 µm							
Material	LSZH							
Colour	Green, red							
Outer cover								
Outer diameter	4 ±0.2 mm							
Thickness	0.8 mm ±0.05 mm							
Material	LSZH -FR							
CPR	Dca-s2, d2, a2							
Colour	Ivory RAL 1015							
Interior protection	Aramids							
SC Connectors								
Connector type	SC							
Polished	APC							
Connection type	Polished							
IL insertion loss	0.2 dB							