



IKUSI
velatia

ONE Compact

Programmable digital amplifier
Compact, light and easy handling



High selectivity



Automatic Gain Control



LTE 4G and LTE 5G



Channel conversion





Configuration over app

ONE Compact

Main Features:

- Ikusi Warranty
- 32 independent VHF/UHF filters
- Input greater dynamic range (allows operation with weaker signals)
- Easy configuration: Configuration copy & software upgrade over app



Software upgrade via app.

An android device (Smartphone or tablet) is required to configure the equipment.

TECHNICAL FEATURES

MODEL		ONE Compact				
REF.		2870				
TV system		AM-TV / DVB-T				
Inputs		5				
		FM	BIII / DAB	UHF 1	UHF 2	UHF 3
Frequency range	MHz	88 - 108	174 - 240	470 -862	470 -790	470 -694
Number of programmable filters		—		32		
Filter bandwidth	MHz	—		6 / 7 / 8 *		
Input level	dB μ V	40 - 78		40 - 100		
AGC (Automatic gain control)		—		Yes		
End-of-channel selectivity \pm 1 MHz	dB	—		45		
Output level	dB μ V	112 **		125 (IMD3 -36 dB) ; 113 ***		
Output regulation	dB	—		20		
Equalization	dB	—		0 - 9		
Noise figure	dB	< 7				
Test output	dB	-20				
Output voltage	VDC mA	—		12 100		
Input voltage	VAC	100 - 240				
Consumption	W	10				
Operating temperature	$^{\circ}$ C	-5 ... +50				
Protection index	IP	IP30				
Dimensions	mm	212 x 159 x 45				

* Depends on the country ; ** DIN45005B (60 dBc) ; *** With 1 mux OFDM