

2-pair telephone cables for outdoor and indoor use



CPT-002N



CPT-002M

MODEL		CPT-002N	CPT-002M
REF.		8264	8265
Number of pairs		2	
Application		Outside	Inside
Drivers	Material	Copper	Copper
	Section	0,50 ±0,01 mm	0,51 mm
	Insulation material	Polyethylene	Polyethylene
Aluminium shielding		Yes	-
Drainage wire		1x0.40mm SN	-
Outer cover	Material	PE Black	Ivory PVC halogen-free and flame-retardant
	Diameter	4.80 ±0.40 mm	4 mm
Maximum electrical resistance (20 °C)		93.8 Ω/Km	93 Ω/Km
Maximum unbalanced resistance (20 °C)		2 %	2 %
Maximum mutual capacity (20 °C)		66 nF/Km	52 nF/Km
Unbalanced maximum capacity (20 °C)		-	510 pF/250 m
Dielectric strength d.c. between conductors (V)		100	500
Colour of the pairs		White-Blue White-Orange	White-Brown Green-Red
Quantity/Packaging (m)		250 m	250 m

- CPT-002N Cat3 telephone cable for outdoor use. With aluminium foil and polyethylene sheath.

- CPT-002M Cat3 telephone cable for indoor use.

* LSZH: Low Smoke Zero Halogen.

It is flame retardant (EN/IEC 60332-3), the density of the smoke produced when the cable is burnt is very low (EN/IEC 61034-2) and the fumes are nontoxic (IEC 60754-2).

* CPR (construction product regulation): Dca s2, d1, a1.

-s (Smoke): Smoke emission performance

-d (droplets): Inflamed droplet / particle fall performance

-a (acidity): This classification provides information on the emission of acid gases during the fire