




Indoor/outdoor fibre box with 12/24 splice tray. IP67 4 input/output ports



MODEL	RSE-024
REF.	8241
Dimensions	200 x 175 x 80 mm
Weight	950 gr
Material	PC-ABS; flame, corrosion and UV resistant
Protection	IP67 - IK10
Temperature range	70°C / -40°C
Inputs/outputs	4
Splice trays	1 (Not expandable)
Splices per tray	1 x 12 or 24 (double height -protector 45mm long)
Splices	12
Splice type	Fusion
Splice protector	Heat Shrink
Cable diameter	See grommets included/available

- In-line encapsulation for wall or pit with 4 configurable ports. Under the same element, it allows fibre trunk fusion for splicing, branching or segregation.
- Supplied with 1 tray with a capacity of 12/24 splices in double height.
- Enclosure especially interesting for industrial areas with long distances and low density compared to domestic housing environments.
- It is an excellent product due to its versatility and quality.

Grommets for input / output ports.			
	Including		Optional
Shape			
Holes	8/10mm	4 x 3.5mm	2 x 3.5mm
Size grommet	25 x 20 x 15 mm		
Quantity	2	2	



1. Protective tube 60 cm - 6 pcs.
2. Grease tube / brush - 1 pc.
3. Heat-shrinkable fusion protector - 24 pcs.
4. White plastic flange 10 cm - 20 pcs.
5. Wall mount - 1 pc.
6. Overhead mounting - 1 pc.
7. Insulating tape - 1 pc.
8. T" key - 1 pc.