

1-way Tap-offs

UDL110

REF. 3226

UDL120

REF. 3228

UDL115

REF. 3227

UDL125

REF. 3229



- Frequency range: 5-2300 MHz.
- Wall fixing, nickle-plated zinc diecast housing (2 screws attached).
- Grounding facilities.
- All ports F female connector.
- DC transit (max +24 V_{DC}, 0.5 A) on the main line.

		UDL-110	UDL-115	UDL-120	UDL-125
Tap loss (± 0.7 dB)	dB	10	15	20	25
Through loss	5 – 862 MHz	≤ 1.1	≤ 1.0	≤ 0.9	≤ 0.5
	950 – 1550 MHz	≤ 1.7		≤ 1.6	≤ 1.3
	1551 – 2300 MHz	≤ 2.3	≤ 2.2	≤ 2.1	≤ 2.0
Directional isolation	5 – 300 MHz	≥ 29	≥ 28	≥ 31	≥ 38
	301 – 862 MHz	≥ 29	≥ 27	≥ 28	≥ 35
	950 – 2300 MHz	≥ 19	≥ 23	≥ 19	≥ 24
Return loss	dB	≥ 15 (TV)			≥ 10 (SAT)
Dimensions	mm	54 x 58 x 26			