

4-way Tap-offs

UDL410

REF. 3235

UDL420

REF. 3237

UDL415

REF. 3236

UDL425

REF. 3238



- Frequency range: 5-2300 MHz.
- Wall fixing, nickle-plated zinc diecast housing (2 screws attached).
- Grounding facilities.
- All ports F female connector.
- DC transit (max +24 V_{DC}, 0.5 A) on the main line.

		UDL-410	UDL-415	UDL-420	UDL-425
Tap loss (±1 dB)	dB	10	15	20	25
Through loss	5 – 862 MHz	≤ 4.0	≤ 1.9	≤ 0.9	≤ 0.6
	950 – 1550 MHz	≤ 4.4	≤ 2.8	≤ 1.5	≤ 1.1
	1551 – 2300 MHz	≤ 4.6	≤ 3.5	≤ 2.1	≤ 1,6
Directional isolation	5 – 300 MHz	≥ 35	≥ 30	≥ 37	≥ 37
	301 – 862 MHz	≥ 33	≥ 30	≥ 33	≥ 37
	950 – 2300 MHz	≥ 29	≥ 23	≥ 25	≥ 27
Tap – to – tap isolation	5 – 300 MHz	≥ 29	≥ 30	≥ 29	≥ 30
	301 – 862 MHz	≥ 26	≥ 28	≥ 26	≥ 26
	950 – 2300 MHz	≥ 24	≥ 28	≥ 24	≥ 26
Return loss	dB	≥ 10 (TV) ≥ 10 (SAT)	≥ 10 (TV) ≥ 10 (SAT)	≥ 12 (TV) ≥ 10 (SAT)	≥ 12 (TV) ≥ 10 (SAT)
Dimensions	mm	76 x 58 x 26			